

Model number: KA4C2DP17L

## KA4C2DP17L Technical Data

### Performance

KA4C2DP17L

Cooling capacity

At 95F/95F(35C/35C)

BTU/H (50/60 Hz)

1500

Watts (50/60 Hz)

440

At 131F/131F(55C/55C)

BTU/H (50/60 Hz)

1500

Watts (50/60 Hz)

440

### Operating temperature Range :

Maximum (F/C)

131(55)

Minimum (F/C)

-20(-29)

### Airflow at 60 Hz:

Internal loop, CFM (Evaporator)

80

External loop CFM (Condenser)

173

Refrigerant type

R134A

Refrigerant charge, oz

5.0

Sound level at 3 ft, dBA

68.2

### Electrical data

Volts

115

Frequency, Hz

60

Running Amps at 95F/95F, 60 Hz

3.0

Running Amps at 131F/131F, 60 Hz

4.0

Starting Amps (Lock Rotor - LRA)

6.9

Power consumption at 95F/95F, 60 Hz Watts

326

Power consumption at 131F/131F, 60 Hz Watts

472

Fuse size, Amps (Maximum)

15

### Enclosure protection

UL Type Internal loop

3R

UL Type External loop

3R

Agency approval

cUL listed

### Temperature controller

Description

Two stage electronic thermostat

Factory Thermostat setting, F

75

Thermostat differential, F

11

### Unit Construction

Material

Galvanized steel

Finish

Textured Baked Powder Beige Paint

### Unit Dimensions

Height, in

17.9

Width, in

12.25

Depth, in

7.31

Weight, Lb

38