

Model number: KA4C3DP21L

## KA4C3DP21L Technical Data

### Performance

KA4C3DP21L

Cooling capacity

At 95F/95F(35C/35C)

BTU/H (50/60 Hz)

2100

Watts (50/60 Hz)

616

At 131F/131F(55C/55C)

BTU/H (50/60 Hz)

1850

Watts (50/60 Hz)

543

### Operating temperature Range :

Maximum (F/C)

131(55)

Minimum (F/C)

-20(-29)

### Airflow at 60 Hz:

Internal loop, CFM (Evaporator)

154

External loop CFM (Condenser)

209

Refrigerant type

R134A

Refrigerant charge, oz

5.5

Sound level at 3 ft, dBA

72.5

### Electrical data

Volts

115

Frequency, Hz

60

Running Amps at 95F/95F, 60 Hz

4.3

Running Amps at 131F/131F, 60 Hz

5.8

Starting Amps (Lock Rotor - LRA)

10

Power consumption at 95F/95F, 60 Hz Watts

480

Power consumption at 131F/131F, 60 Hz Watts

617

Fuse size, Amps (Maximum)

15

### Enclosure protection

UL Type Internal loop (Evaporator)

3R

UL Type External loop (Condenser)

3R

Agency approval

cUL listed

### Temperature controller

Description

Two stage electronic thermostat

Factory Thermostat setting, F

75

Thermostat differential, F

11

### Unit Construction

Material

Galvanized steel

Finish

Textured Baked Powder Beige Paint

### Unit Dimensions

Height, in

21

Width, in

13.6

Depth, in

7.32

Weight, Lb

45