

Model number: KNA4C3DP21L

KNA4C3DP21L

Technical Data

Performance

Cooling capacity	
At 95F/95F(35C/35C)	
BTU/H(50/60 Hz)	2500
Watts (50/60 Hz)	733
At 131F/131F(55C/55C)	
BTU/H (50/60 Hz)	2300
Watts (50/60 Hz)	674
Operating temperature Range :	
Maximum (F/C)	131(55)
Minimum (F/C)	-20(-29)
Airflow at 60 Hz:	
Internal loop, CFM (Evaporator)	171
External loop CFM (Condenser)	173
Refrigerant type	R134A
Refrigerant charge, oz	7.5
Sound level at 3 ft, dBA	69.2

Electrical data

Volts	115
Frequency, Hz	60
Running Amps at 95F/95F, 60 Hz	4.3
Running Amps at 131F/131F, 60 Hz	5.6
Starting Amps (Lock Rotor - LRA)	16
Power consumption at 95F/95F, 60 Hz Watts	475
Power consumption at 131F/131F, 60 Hz Watts	627
Fuse size, Amps (Maximum)	15

Enclosure protection

UL Type Internal loop (Evaporator)	NEMA4/4X
UL Type External loop (Condenser)	NEMA4/4X
Agency approval	cUL Listed

Temperature controller

Description	Electronic thermostat
Factory Thermostat setting, F	75
Thermostat differential, F	11

Unit Construction

Material	Galvanized steel
Finish	Textured Baked Powder Beige Paint or SS

Unit Dimensions

Height, in	21
Width, in	12
Depth, in	10.2
Weight, Lb	53