

KA4C5DP33L / K2A4C5DP33L

Model number: KA4C5DP33L

Technical Data

K2A4C5DP33L

Performance

KA4C5DP33L

K2A4C5DP33L

Cooling capacity

At 95F/95F(35C/35C)

BTU/H (50/60 Hz)

4000

4000

Watts (50/60 Hz)

1173

1173

At 131F/131F(55C/55C)

BTU/H (50/60 Hz)

4000

4000

Watts (50/60 Hz)

1173

1173

Operating temperature Range :

Maximum (F/C)

131(55)

131(55)

Minimum (F/C)

-20(-29)

-20(-29)

Airflow at 60 Hz:

Internal loop, CFM (Evaporator)

191

191

External loop CFM (Condenser)

253

253

Refrigerant type

R134A

R134A

Refrigerant charge, oz

20.0

20.0

Sound level at 3 ft, dBA

69.7

69.6

Electrical data

Volts

115

230

Frequency, Hz

60

60

Running Amps at 95F/95F, 60 Hz

7.0

3.1

Running Amps at 131F/131F, 60 Hz

9.3

4.5

Starting Amps (Lock Rotor - LRA)

39

23

Power consumption at 95F/95F, 60 Hz Watts

724

587

Power consumption at 131F/131F, 60 Hz Watts

1005

978

Fuse size, Amps (Maximum)

15

15

Enclosure protection

UL Type Internal loop (Evaporator)

3R

3R

UL Type External loop (Condenser)

3R

3R

Agency approval

cUL listed

cUL listed

Temperature controller

Description

Electronic thermostat

Electronic thermostat

Factory Thermostat setting, F

75

75

Thermostat differential, F

11

11

Unit Construction

Material

Galvanized steel

Galvanized steel

Finish

Textured Baked Powder Beige Paint Textured Baked Powder Beige Paint

Unit Dimensions

Height, in

33.9

33.9

Width, in

17.1

17.1

Depth, in

8.1

8.1

Weight, Lb

95

95