

Model number: K3A4C5DP38L

## K3A4C5DP38L

### Technical Data

#### Performance

K3A4C5DP38L

##### Cooling capacity

At 95F/95F(35C/35C)

BTU/H (50/60 Hz)

4800

Watts (50/60 Hz)

1408

At 131F/131F(55C/55C)

BTU/H (50/60 Hz)

5000

Watts (50/60 Hz)

1466

##### Operating temperature Range :

Maximum (F/C)

131(55)

Minimum (F/C)

0(-8)

##### Airflow at 60 Hz:

Internal loop, CFM (Evaporator)

191

External loop CFM (Condenser)

253

Refrigerant type

R134A

Refrigerant charge, oz

20.0

Sound level at 3 ft, dBA

69.7

#### Electrical data

Phase

3

Volts

480

Frequency, Hz

60

Running Amps at 95F/95F, 60 Hz

1.7

Running Amps at 131F/131F, 60 Hz

2.0

Starting Amps (Lock Rotor - LRA)

15

Power consumption at 95F/95F, 60 Hz Watts

770

Power consumption at 131F/131F, 60 Hz Watts

Fuse size, Amps (Maximum)

15

#### Enclosure protection

UL Type Internal loop (Evaporator)

3R

UL Type External loop (Condenser)

3R

Agency approval

cUL listed

#### Temperature controller

Description

Electronic thermostat

Factory Thermostat setting, F

75

Thermostat differential, F

11

#### Unit Construction

Material

Galvanized steel

Finish

Textured Baked Powder Beige Paint

#### Unit Dimensions

Height, in

38.9

Width, in

17.1

Depth, in

8.3

Weight, Lb

115