

Model number: K3A4C5DP38L

K3A4C5DP38L

Technical Data

Performance

K3A4C5DP38L

Cooling capacity

At 95F/95F(35C/35C)

BTU/H (50/60 Hz)

4800

Watts (50/60 Hz)

1408

At 131F/131F(55C/55C)

BTU/H (50/60 Hz)

5000

Watts (50/60 Hz)

1466

Operating temperature Range :

Maximum (F/C)

131(55)

Minimum (F/C)

0(-8)

Airflow at 60 Hz:

Internal loop, CFM (Evaporator)

191

External loop CFM (Condenser)

253

Refrigerant type

R134A

Refrigerant charge, oz

20.0

Sound level at 3 ft, dBA

69.7

Electrical data

Phase

3

Volts

480

Frequency, Hz

60

Running Amps at 95F/95F, 60 Hz

1.7

Running Amps at 131F/131F, 60 Hz

2.0

Starting Amps (Lock Rotor - LRA)

15

Power consumption at 95F/95F, 60 Hz Watts

770

Power consumption at 131F/131F, 60 Hz Watts

Fuse size, Amps (Maximum)

15

Enclosure protection

UL Type Internal loop (Evaporator)

3R

UL Type External loop (Condenser)

3R

Agency approval

cUL listed

Temperature controller

Description

Electronic thermostat

Factory Thermostat setting, F

75

Thermostat differential, F

11

Unit Construction

Material

Galvanized steel

Finish

Textured Baked Powder Beige Paint

Unit Dimensions

Height, in

38.9

Width, in

17.1

Depth, in

8.3

Weight, Lb

115