

KA4C7DP43L / K2A4C7DP43L

Technical Data

**Model number: KA4C7DP43L /
K2A4C7DP43L**

Performance

Cooling capacity		
At 95F/95F(35C/35C)		
BTU/H (50/60 Hz)	5500	5500
Watts (50/60 Hz)	1613	1613
At 131F/131F(55C/55C)		
BTU/H (50/60 Hz)	5500	5500
Watts (50/60 Hz)	1613	1613

Operating temperature Range :

Maximum (F/C)	131(55)	131(55)
Minimum (F/C)	-20(-29)	-20(-29)

Airflow at 60 Hz:

Internal loop, CFM (Evaporator)	264	264
External loop CFM (Condenser)	460	460
Refrigerant type	R134A	R134A
Refrigerant charge, oz	26.0	26.0
Sound level at 3 ft, dBA	77.5	77.5

Electrical data

Volts	115	230
Frequency, Hz	60	60
Running Amps at 95F/95F, 60 Hz	10.4	
Running Amps at 131F/131F, 60 Hz	13.8	6.7
Starting Amps (Lock Rotor - LRA)	48.3	
Power consumption at 95F/95F, 60 Hz Watts	1103	
Power consumption at 131F/131F, 60 Hz Watts	1510	
Fuse size, Amps (Maximum)	20	15

Enclosure protection

UL Type Internal loop (Evaporator)	3R	3R
UL Type External loop (Condenser)	3R	3R
Agency approval	cUL listed	cUL listed

Temperature controller

Description	Electronic thermostat	Electronic thermostat
Factory Thermostat setting, F	75	75
Thermostat differential, F	11	11

Unit Construction

Material	Galvanized steel	Galvanized steel
Finish	Textured Baked Powder Beige Paint	Textured Baked Powder Beige Paint

Unit Dimensions

Height, in	43.4	43.4
Width, in	17.1	17.1
Depth, in	9.1	9.1
Weight, Lb	125	125