

**KNA4C7DP43L / K2NA4C7DP43L****Technical Data**

**Model number: KNA4C7DP43L**  
**K2NA4C7DP43L**

**Performance**

Cooling capacity

At 95F/95F(35C/35C)

BTU/H (50/60 Hz)

Watts (50/60 Hz)

At 131F/131F(55C/55C)

BTU/H (50/60 Hz)

Watts (50/60 Hz)

**Operating temperature Range :**

Maximum (F/C)

Minimum (F/C)

**Airflow at 60 Hz:**

Internal loop, CFM (Evaporator)

External loop CFM (Condenser)

Refrigerant type

Refrigerant charge, oz.

Sound level at 3 ft., dBA

KNA4C7DP43L

K2NA4C7DP43L

5500

1613

5500

1613

131(55)

-20(-29)

264

460

R134A

26.0

77.5

5500

1613

5500

1613

131(55)

-20(-29)

264

460

R134A

26.0

77.5

**Electrical data**

Volts

Frequency, Hz

Running Amps at 95F/95F, 60 Hz

Running Amps at 131F/131F, 60 Hz

Starting Amps (Lock Rotor - LRA)

Power consumption at 95F/95F, 60 Hz Watts

Power consumption at 131F/131F, 60 Hz Watts

Fuse size, Amps (Maximum)

115

60

10.4

13.8

48.3

1103

1510

20

230

60

6.7

27

15

**Enclosure protection**

UL Type Internal loop (Evaporator)

UL Type External loop (Condenser)

Agency approval

NEMA4

NEMA4

cUL listed

NEMA4

NEMA4

cUL listed

**Temperature controller**

Description

Factory Thermostat setting, F

Thermostat differential, F

Electronic thermostat

75

11

Electronic thermostat

75

11

**Unit Construction**

Material

Finish

Galvanized steel

Textured Baked Powder Beige Paint or SS

Galvanized steel

Textured Baked Powder Beige Paint or SS

**Unit Dimensions**

Height, in

Width, in

Depth, in

Weight, Lb

43.4

17.2

9.8

125

43.4

17.2

9.8

125