

KA4C9DP47L / K2A4C9DP47L

**Model number: KA4C9DP47L /
K2A4C9DP47L**

Technical Data

Performance

	KA4C9DP47L	KA4C9DP47L
Cooling capacity		
At 95F/95F(35C/35C)		
BTU/H (50/60 Hz)	7400	7400
Watts (50/60 Hz)	2170	2170
At 131F/131F(55C/55C)		
BTU/H(50/60 Hz)	7400	7400
Watts (50/60 Hz)	2170	2170
Operating temperature Range :		
Maximum (F/C)	131(55)	131(55)
Minimum (F/C)	-20(-29)	-20(-29)
Airflow at 60 Hz:		
Internal loop, CFM (Evaporator)	350	350
External loop CFM (Condenser)	442	442
Refrigerant type	R134A	R134A
Refrigerant charge, oz	29.0	20.0
Sound level at 3 ft, dBA	74.7	74.7

Electrical data

Volts	115	230
Frequency, Hz	60	60
Running Amps at 95F/95F, 60 Hz	13.4	6.4
Running Amps at 131F/131F, 60 Hz	19.2	8.7
Starting Amps (Lock Rotor - LRA)	57	38
Power consumption at 95F/95F, 60 Hz Watts	1409	1428
Power consumption at 131F/131F, 60 Hz Watts	2198	1981
Fuse size, Amps (Maximum)	30	15

Enclosure protection

UL Type Internal loop (Evaporator)	3R	3R
UL Type External loop (Condenser)	3R	3R
Agency approval	cUL listed	cUL listed

Temperature controller

Description	Electronic thermostat	Electronic thermostat
Factory Thermostat setting, F	75	75
Thermostat differential, F	11	11

Unit Construction

Material	Galvanized steel	Galvanized steel
Finish	Textured Baked Powder Beige Paint	Textured Baked Powder Beige Paint

Unit Dimensions

Height, in	47	47
Width, in	17.1	17.1
Depth, in	9.1	9.1
Weight, Lb	135	135