

Model number: KNA4C9DP47L		KNA4C9DP47L / K2NA4C9DP47L	
K2NA4C9DP47L		Technical Data	
Performance		KNA4C9DP47L	K2NA4C9DP47L
Cooling capacity			
At 95F/95F(35C/35C)			
BTU/H (50/60 Hz)		7400	7400
Watts (50/60 Hz)		2170	2170
At 131F/131F(55C/55C)			
BTU/H (50/60 Hz)		7400	7400
Watts (50/60 Hz)		2170	2170
Operating temperature Range :			
Maximum (F/C)		131(55)	131(55)
Minimum (F/C)		-20(-29)	-20(-29)
Airflow at 60 Hz:			
Internal loop, CFM (Evaporator)		350	350
External loop CFM (Condenser)		442	442
Refrigerant type		R134A	R134A
Refrigerant charge, oz		29.0	20.0
Sound level at 3 ft, dBA		74.7	74.7
Electrical data			
Volts		115	230
Frequency, Hz		60	60
Running Amps at 95F/95F, 60 Hz		13.4	6.4
Running Amps at 131F/131F, 60 Hz		19.2	8.7
Starting Amps (Lock Rotor - LRA)		57	38
Power consumption at 95F/95F, 60 Hz Watts		1409	1428
Power consumption at 131F/131F, 60 Hz Watts		2198	1981
Fuse size, Amps (Maximum)		30	15
Enclosure protection			
UL Type Internal loop (Evaporator)		NEMA4	NEMA4
UL Type External loop (Condenser)		NEMA4	NEMA4
Agency approval		cUL listed	cUL listed
Temperature controller			
Description		Electronic thermostat	Electronic thermostat
Factory Thermostat setting, F		75	75
Thermostat differential, F		11	11
Unit Construction			
Material		Galvanized steel	Galvanized steel
Finish		Textured Baked Powder Beige Paint or SS	Textured Baked Powder Beige Paint or SS
Unit Dimensions			
Height, in		47	47
Width, in		17.1	17.1
Depth, in		9.1	9.1
Weight, Lb		135	135