

Model number: K3NA6C14DP50L

## K3NA6C14DP50L

### Technical Data

#### Performance

K3NA6C14DP50L

Cooling capacity

At 95F/95F(35C/35C)

BTU/H (50/60 Hz)

11700/13000

Watts (50/60 Hz)

3410/3810

At 131F/131F(55C/55C)

BTU/H (50/60 Hz)

10800/12000

Watts (50/60 Hz)

3570/3519

#### Operating temperature Range :

Maximum (F/C)

131(55)

Minimum (F/C)

-20(-29)

#### Airflow at 60 Hz:

Internal loop, CFM (Evaporator)

409

External loop CFM (Condenser)

874

Refrigerant type

R410A

Refrigerant charge, oz

40.0

Sound level at 3 ft, dBA

72.8

#### Electrical data

Volts

480

Phase

3

Frequency, Hz

60

Running Amps at 95F/95F, 60 Hz

Running Amps at 131F/131F, 60 Hz

5.0

Starting Amps (Lock Rotor - LRA)

30

Power consumption at 95F/95F, 60 Hz Watts

Power consumption at 131F/131F, 60 Hz Watts

Fuse size, Amps (Maximum)

15

#### Enclosure protection

UL Type Internal loop (Evaporator)

NEMA4

UL Type External loop (Condenser)

NEMA4

Agency approval

cUL listed

#### Temperature controller

Description

Electronic thermostat

Factory Thermostat setting, F

75

Thermostat differential, F

11

#### Unit Construction

Material

Galvanized steel

Finish

Textured Baked Powder Beige Paint or SS

#### Unit Dimensions

Height, in

50

Width, in

20.1

Depth, in

12

Weight, Lb

207