

**K3A4C7DP52L / K3A4C9DP52L****Model number: K3A4C7DP52L/  
K3A4C9DP52L****Technical Data****Performance**

## Cooling capacity

At 95F/95F(35C/35C)

BTU/H (50/60 Hz)

Watts (50/60 Hz)

At 131F/131F(55C/55C)

BTU/H (50/60 Hz)

Watts (50/60 Hz)

**Operating temperature Range :**

Maximum (F/C)

Minimum (F/C)

**Airflow at 60 Hz:**

Internal loop, CFM (Evaporator)

External loop CFM (Condenser)

Refrigerant type

Refrigerant charge, oz

Sound level at 3 ft, dBA

K3A4C7DP52L

K3A4C9DP52L

6300

1848

6700

1965

131(55)

0(-18)

264

460

R134A

29.0

74.7

8100

2375

7900

2317

131(55)

0(-18)

350

442

R134A

29.0

74.7

**Electrical data**

Phase

Volts

Frequency, Hz

Running Amps at 95F/95F, 60 Hz

Running Amps at 131F/131F, 60 Hz

Starting Amps (Lock Rotor - LRA)

Power consumption at 95F/95F, 60 Hz Watts

Power consumption at 131F/131F, 60 Hz Watts

Fuse size, Amps (Maximum)

3

480

60

2.0

3.0

16

890

911

15

3

480

60

3.2

4.0

16

961

15

**Enclosure protection**

UL Type Internal loop (Evaporator)

UL Type External loop (Condenser)

Agency approval

3R

3R

cUL listed

3R

3R

cUL listed

**Temperature controller**

Description

Factory Thermostat setting, F

Thermostat differential, F

Electronic thermostat

75

11

Electronic thermostat

75

11

**Unit Construction**

Material

Finish

Galvanized steel

Galvanized steel

Textured Baked Powder Beige Paint Textured Baked Powder Beige Paint

**Unit Dimensions**

Height, in

Width, in

Depth, in

Weight, Lb

51.9

17.1

9.3

160

51.9

17.1

9.3

164