

K3NA4C7DP52L / K3NA4C9DP52L

**Model number: K3NA4C7DP52L/
K3NA4C9DP52L**

Technical Data

Performance	K3NA4C7DP52L	K3NA4C9DP52L
Cooling capacity		
At 95F/95F(35C/35C)		
BTU/H (50/60 Hz)	6300	8100
Watts (50/60 Hz)	1848	2375
At 131F/131F(55C/55C)		
BTU/H (50/60 Hz)	6700	7900
Watts (50/60 Hz)	1965	2317
Operating temperature Range :		
Maximum (F/C)	131(55)	131(55)
Minimum (F/C)	0(-18)	0(-18)
Airflow at 60 Hz:		
Internal loop, CFM (Evaporator)	264	350
External loop CFM (Condenser)	460	442
Refrigerant type	R134A	R134A
Refrigerant charge, oz	29.0	29.0
Sound level at 3 ft, dBA	74.4	74.4
Electrical data		
Volts	480	480
Phase	3	3
Frequency, Hz	60	60
Running Amps at 95F/95F, 60 Hz	2	3.2
Running Amps at 131F/131F, 60 Hz	3.0	4.0
Starting Amps (Lock Rotor - LRA)	16.0	16.0
Power consumption at 95F/95F, 60 Hz Watts	890	961
Power consumption at 131F/131F, 60 Hz Watts	911	
Fuse size, Amps (Maximum)	15	15
Enclosure protection		
UL Type Internal loop	NEMA4	NEMA4
UL Type External loop	NEMA4	NEMA4
Agency approval	cUL listed	cUL listed
Temperature controller		
Description	Electronic thermostat	Electronic thermostat
Factory Thermostat setting, F	75	75
Thermostat differential, F	11	11
Unit Construction		
Material	Galvanized steel	Galvanized steel
Finish	Textured Baked Powder Beige Paint	Textured Baked Powder Beige Paint
Unit Dimensions		
Height, in	52	52
Width, in	17.4	17.4
Depth, in	9.9	9.9
Weight, Lb	160	160