

| Model | NEMA Rating | UL/CUL Listed or Recognized | BTU/H Rating | 95/95 Rating | Ambient Temp. | | | | Volts | Hz | * Running Amps | Approx. Weight | |
|---------------|-------------|-----------------------------|--------------|--------------|---------------|------|------|------|-------|----|----------------|----------------|----|
| | | | | | °F | | °C | | | | | lbs | kg |
| | | | | | Max. | Min. | Max. | Min. | | | | | |
| K3NA4C7DP52L | 4 | Listed | 7000 | 6300 | 131 | 0 | 55 | -18 | 480 | 60 | 3.0 | 160 | 72 |
| K3NA4C9DP52L | 4 | Listed | 9000 | 8100 | 131 | 0 | 55 | -18 | 480 | 60 | 4.0 | 164 | 75 |
| K3NA4C7DP52LV | 4X | Listed | 7000 | 6300 | 131 | 0 | 55 | -18 | 480 | 60 | 3.0 | 160 | 72 |
| K3NA4C9DP52LV | 4X | Listed | 9000 | 8100 | 131 | 0 | 55 | -18 | 480 | 60 | 4.0 | 164 | 75 |

* Rating shown is for operation at maximum ambient temperature.



NEMA TYPE 4 OR 4X MAINTAINED



STANDARD FEATURES

- Built-in Condensate Evaporator
- CFC-Free Refrigerant
- Closed-Loop Cooling
- Condenser Impeller Speed Controller
- Epoxy-Coated Condenser Coil
- External junction box for permanent wiring connections
- Heavy-duty Steel Shell
- Internal Corrosion Protection (NEMA 4X models)
- Low Temperature Control Thermostat
- NEMA 4 or 4X Rating Maintained (UL50)
- Phase Sequence/Phase Loss Detector/Under Voltage Monitor
- Stainless Steel Shell (NEMA 4X models)
- Textured Baked Powder Finish
- UL/CUL Listed

ACCESSORIES AND OPTIONS


- Cooling Effect Detector
- Enclosure Heater
- Filter
- Filter Recoating Adhesive
- Lead-Lag Controller
- Remote Thermostat Relay
- Replacement Filters
- Short Cycle Protector
- Special paint finishes

Find additional information on this model at kooltronic.com, or use the Technical Documents QR code below.



Technical Documents



- ① CONDENSER AIR INLET (Ambient Air In)
- ② CONDENSER OUTLET (Warm Ambient Air Out)
- ③ WARM AIR RETURN FROM ENCLOSURE
- ④ COOL AIR OUTLET TO ENCLOSURE





PERFORMANCE CHARTS



Operation within shaded area not recommended.

Many popular units are available as 3D solid models for customer system integration. Please contact Kooltronic for details.



MOUNTING PLAN

Dimensions, inches [mm], are for reference only and are subject to change. dp52/lv.qxd 4/20/12

DESCRIPTION

The *Guardian/GuardianX 480 Volt* Indoor/Outdoor Air Conditioners are designed specifically for **NEMA 4** or **4X** enclosure applications that require washdown or are subject to outdoor storm conditions. All *Guardian* models have a **NEMA 4** Rating. The *GuardianX*, with the **NEMA 4X** Rating, is offered with a Stainless Steel Shell and Internal Corrosion Protection. These Air Conditioners have been engineered to operate under the most demanding industrial applications. The components used in these models have been specially designed and tested to maintain cooling efficiency in temperature controlled enclosures in bottling plants, the automotive industry and other commercial/manufacturing applications.

With Epoxy-coated condenser coils and tubing, the closed-loop cooling system of the *Guardian/GuardianX 480 Volt Series* offers added security by providing an operating environment safe from harsh ambient conditions.

The features engineered into all of the *Guardian/GuardianX 480 Volt Series* models make them a tamper-resistant choice for external applications. Combined with a NEMA 4 Rating, with all models UL/CUL Listed, the *Guardian Series* is an excellent choice for telecommunications or other outdoor cabinet applications.

STANDARD FEATURES

CLOSED-LOOP COOLING: The enclosure interior airflow system is isolated from the ambient airflow system. Ambient air can not invade the cool, dehumidified sensitive component compartment.

CONDENSER IMPELLER SPEED CONTROLLER: A solid state sensor reacting to the condenser coil temperature modulates the condenser impeller between minimum and maximum speed based on the coil temperature. This reduces noise levels, fan cycling, compressor cycling and prevents the unit from freezing.

GASKETING: All units are fully gasketed for tight, leakproof installation, in compliance with the NEMA 4 Enclosure Rating.

HEAVY-DUTY STEEL SHELL: Precision-engineered heavy gauge steel construction of all shells and blowers insures Air Conditioners will stand up under tough applications.

INSULATION: All cold components, lines and the evaporator compartment are insulated with high-performance insulation for maximum efficiency.

LOW TEMPERATURE CONTROL THERMOSTAT: Thermostatic Low Temperature Control prevents over-cooling and provides energy-efficient operation.

POWER: 480 Volt.

QUALITY ASSURANCE: Refrigeration system components are kept sealed until charged with refrigerant; all brazed joints are thoroughly leak-tested; each unit is functionally tested before shipment.

REFRIGERANT: CFC-free R134a Refrigerant is used in the *Guardian/GuardianX Series DP52* Air Conditioners.

TEXTURED BAKED POWDER FINISH: Durable, baked-on textured beige powder finish is standard. Other finishes are available.

UL/CUL LISTED: The *Guardian/GuardianX Series DP52* is UL/CUL Listed.

ACCESSORIES AND OPTIONS*

COOLING EFFECT DETECTOR: A thermostat is mounted inside the cabinet and attached to a sensor in the warm air return. When the air temperature increases to the set point, a signal is sent to a terminal block. User-installed wiring from the terminal block to local and/or remote warning devices (*light, bell, siren, etc.*) can be for normally open or normally closed operation.

ENCLOSURE HEATER: Fin strip heater, installed singly, used to maintain internal enclosure temperature, under cold operating conditions.

FILTERS: Multi-layer grid of sturdy, corrugated aluminum in an aluminum frame. May be reused after washing off accumulations and spraying with A-16 Recoating Adhesive.

FILTER RECOATING ADHESIVE: This compound is a superior product for recoating filters after washing. The adhesives penetrate dirt layers to keep the filter surface tacky for longer effective performance between washings.

INTERNAL CORROSION PROTECTION: An air cured coating is sprayed on copper lines and brazed joints on the condenser side, providing a degree of protection from corrosive environments. This coating will withstand 1000 hours of salt spray per the ASTM B 117 test method. Also see Stainless Steel Cabinet or Integrity NEMA 4/4X Air Conditioners. **NOTE:** Severe operational environments such as waste water treatment and salt spray are likely to cause corrosion failure over a period of time regardless of coating. **Warranty:** Corrosive conditions may effect the warranty coverage. Consult factory for warranty limitations in corrosive environments. **NOTE:** For additional corrosion protection options, contact factory. Internal Corrosion Protection and Stainless Steel Shell are necessary in order to maintain **NEMA 4X** Rating for *GuardianX DP52*.

STAINLESS STEEL SHELL: For applications in corrosive or other hostile environments where chemical/moisture combinations are present. Stainless Steel Shell and Internal Corrosion Protection are necessary in order to maintain **NEMA 4X** Rating for *GuardianX DP52*.

SHORT CYCLE PROTECTOR: Protects the compressor from possible damage due to harmful short cycling, (frequent starting) where temperature controls enable the compressor to restart frequently or after a power interruption.

Other voltages and frequencies*

REPLACEMENT FILTER: Filter consisting of a multi-layer grid of sturdy corrugated aluminum, securely held in a one-piece aluminum frame.

The DP52 optional filter Part No. is 8001F (8.00" x 16.00" x 0.38" [203.2mm x 406.4mm x 9.7mm])

Special paint finishes*

*Contact KOOLTRONIC for more information.