

K3NA6C26DP60L

Technical Data

Model number: K3NA6C26DP60L

Performance

K3NA6C26DP60L

Cooling capacity

At 95F/95F(35C/35C)

BTU/H (50/60 Hz)

18300/22800

Watts (50/60 Hz)

5370/6686

At 131F/131F(55C/55C)

BTU/H (50/60 Hz)

15300/19000

Watts (50/60 Hz)

4486/5570

Operating temperature Range :

Maximum (F/C)

131(55)

Minimum (F/C)

-20(-29)

Airflow at 60 Hz:

Internal loop, CFM (Evaporator)

694

External loop CFM (Condenser)

1327

Refrigerant type

R410A

Refrigerant charge, oz

77.0

Sound level at 3 ft, dBA

74.9

Electrical data

Volts

480

Phase

3

Frequency, Hz

60

Running Amps at 95F/95F, 60 Hz

6.9

Running Amps at 131F/131F, 60 Hz

7.4

Starting Amps (Lock Rotor - LRA)

34

Power consumption at 95F/95F, 60 Hz Watts

2300

Power consumption at 131F/131F, 60 Hz Watts

2500

Fuse size, Amps (Maximum)

15

Enclosure protection

UL Type Internal loop (Evaporator)

NEMA4

UL Type External loop (Condenser)

NEMA4

Agency approval

cUL listed

Temperature controller

Description

Electronic thermostat

Factory Thermostat setting, F

75

Thermostat differential, F

11

Unit Construction

Material

Galvanized steel

Finish

Textured Baked Powder Beige Paint or SS

Unit Dimensions

Height, in

60.2

Width, in

24.1

Depth, in

13

Weight, Lb

262