

KA6C4NPT33L / K2A6C4NPT33L

**Model number: KA6C4NPT33L /
K2A6C4NPT33L**

Technical Data

| Performance | KA6C4NPT33L | K2A6C4NPT33L |
|---|----------------------------------|----------------------------------|
| Cooling capacity At 95F/95F(35C/35C) | | |
| BTU/H (50/60 Hz) | 3200 | 3200 |
| Watts (50/60 Hz) | 938 | 938 |
| At 131F/131F(55C/55C) | | |
| BTU/H (50/60 Hz) | 2900 | 2900 |
| Watts (50/60 Hz) | 850 | 850 |
| Operating temperature Range : | | |
| Maximum (F/C) | 131(55) | 131(55) |
| Minimum (F/C) | -20(-29) | -20(-29) |
| Airflow at 60 Hz: | | |
| Internal loop, CFM (Evaporator) | 169 | 169 |
| External loop CFM (Condenser) | 211 | 211 |
| Refrigerant type | R410A | R410A |
| Refrigerant charge, oz | 18.0 | 20.0 |
| Sound level at 3 ft, dBA | 68.1 | 68.1 |
| Electrical data | | |
| Volts | 115 | 230 |
| Frequency, Hz | 60 | 60 |
| Running Amps at 95F/95F, 60 Hz | 5.7 | 3.0 |
| Running Amps at 131F/131F, 60 Hz | 7.8 | 3.9 |
| Starting Amps (Lock Rotor - LRA) | 26 | 17.7 |
| Power consumption at 95F/95F, 60 Hz Watts | 625 | 670 |
| Power consumption at 131F/131F, 60 Hz Watts | 846 | 875 |
| Fuse size, Amps (Maximum) | 15 | 15 |
| Enclosure protection | | |
| UL Type Internal loop (Evaporator) | 3R | 3R |
| UL Type External loop (Condenser) | 3R | 3R |
| Agency approval | cUL listed | cUL listed |
| Temperature controller | | |
| Description | Electronic thermostat | Electronic thermostat |
| Factory Thermostat setting, F | 75 | 75 |
| Thermostat differential, F | 11 | 11 |
| Unit Construction | | |
| Material | Galvanized steel | Galvanized steel |
| Finish | Textured Baked Powder Grey Paint | Textured Baked Powder Grey Paint |
| Unit Dimensions | | |
| Height, in | 32.8 | 32.8 |
| Width, in | 12 | 12 |
| Depth, in | 9.55 | 9.55 |
| Weight, Lb | 71 | 71 |