

KA6C10NPT47L / K2A6C10NPT47L

**Model number: KA6C10NPT47L /
K2A6C10NPT47L**

Technical Data

Performance

Cooling capacity

At 95F/95F(35C/35C)

BTU/H (50/60 Hz)

Watts (50/60 Hz)

At 131F/131F(55C/55C)

BTU/H (50/60 Hz)

Watts (50/60 Hz)

Operating temperature Range :

Maximum (F/C)

Minimum (F/C)

Airflow at 60 Hz:

Internal loop, CFM (Evaporator)

External loop CFM (Condenser)

Refrigerant type

Refrigerant charge, oz

Sound level at 3 ft, dBA

KA6C10NPT47L

K2A6C10NPT47L

7730/8300

7730/8300

2266/2434

2266/2434

6705/7200

6705/7200

1966/2111

1966/2111

131(55)

131(55)

-20(-29)

-20(-29)

295

295

537

537

R410A

R410A

26.0

26.0

72

72

Electrical data

Volts

Frequency, Hz

Running Amps at 95F/95F, 60 Hz

Running Amps at 131F/131F, 60 Hz

Starting Amps (Lock Rotor - LRA)

Power consumption at 95F/95F, 60 Hz Watts

Power consumption at 131F/131F, 60 Hz Watts

Fuse size, Amps (Maximum)

115

230

60

60

14.8

7.1

19.4

8.7

57

26

1618

1602

2165

2002

30

15

Enclosure protection

UL Type Internal loop (Evaporator)

UL Type External loop (Condenser)

Agency approval

3R

3R

3R

3R

cUL listed

cUL listed

Temperature controller

Description

Factory Thermostat setting, F

Thermostat differential, F

Electronic thermostat

Electronic thermostat

75

75

11

11

Unit Construction

Material

Finish

Galvanized steel

Galvanized steel

Textured Baked Powder Grey Paint

Textured Baked Powder Grey Paint

Unit Dimensions

Height, in

Width, in

Depth, in

Weight, Lb

47.2

47.2

15.1

15.1

12.2

12.2

128

128

K2A6C13NPT47L**Technical Data**

Model number: K2A6C13NPT47L

Performance

K2A6C13NPT47L

Cooling capacity

At 95F/95F(35C/35C)

BTU/H (50/60 Hz)

8770/9700

Watts (50/60 Hz)

2571/2844

At 131F/131F(55C/55C)

BTU/H (50/60 Hz)

9041/10000

Watts (50/60 Hz)

2651/2932

Operating temperature Range :

Maximum (F/C)

131(55)

Minimum (F/C)

-20(-29)

Airflow at 60 Hz:

Internal loop, CFM (Evaporator)

295

External loop CFM (Condenser)

556

Refrigerant type

R410A

Refrigerant charge, oz

30.0

Sound level at 3 ft, dBA

74

Electrical data

Volts

230

Frequency, Hz

60

Running Amps at 95F/95F, 60 Hz

9

Running Amps at 131F/131F, 60 Hz

12.7

Starting Amps (Lock Rotor - LRA)

33

Power consumption at 95F/95F, 60 Hz Watts

1968

Power consumption at 131F/131F, 60 Hz Watts

2562

Fuse size, Amps (Maximum)

20

Enclosure protection

UL Type Internal loop (Evaporator)

3R

UL Type External loop (Condenser)

3R

Agency approval

cUL listed

Temperature controller

Description

Electronic thermostat

Factory Thermostat setting, F

75

Thermostat differential, F

11

Unit Construction

Material

Galvanized steel

Finish

Textured Baked Powder Grey Paint

Unit Dimensions

Height, in

47.2

Width, in

15.1

Depth, in

12.2

Weight, Lb

131