

Model number: K2A6C16NPT52L

K2A6C16NPT52 Technical Data

Performance

K2A6C16NPT52L

Cooling capacity

At 95F/95F(35C/35C)

BTU/H (50/60 Hz)

11300/13300

Watts (50/60 Hz)

3313/3900

At 125F/125F(55C/55C)

BTU/H (50/60 Hz)

9600/11400

Watts (50/60 Hz)

2815/3343

Operating temperature Range :

Maximum (F/C)

125(52)

Minimum (F/C)

-20(-29)

Airflow at 60 Hz:

Internal loop, CFM (Evaporator)

372

External loop CFM (Condenser)

914

Refrigerant type

R410A

Refrigerant charge, oz

46.0

Sound level at 3 ft, dBA

75.6

Electrical data

Volts

230

Frequency, Hz

60

Running Amps at 95F/95F, 60 Hz

14.4

Running Amps at 125F/125F, 60 Hz

18

Starting Amps (Lock Rotor - LRA)

44

Power consumption at 95F/95F, 60 Hz Watts

3250

Power consumption at 125F/125F, 60 Hz Watts

4207

Fuse size, Amps (Maximum)

30

Enclosure protection

UL Type Internal loop (Evaporator)

NEMA12

UL Type External loop (Condenser)

NEMA12

Agency approval

cUL listed

Temperature controller

Description

Electronic thermostat

Factory Thermostat setting, F

75

Thermostat differential, F

11

Unit Construction

Material

Galvanized steel

Finish

Textured Baked Powder Grey Paint

Unit Dimensions

Height, in

52.7

Width, in

17.3

Depth, in

14.1

Weight, Lb

189