

KA4C5RML / K2A4C5RML**Technical Data****Model number: KA4C5RML /
K2A4C5RML****Performance**

	KA4C5RML	K2A4C5RML
Cooling capacity		
At 95F/95F(35C/35C)		
BTU/H (50/60 Hz)	4400	4150/4030
Watts (50/60 Hz)	1290	1217/1181
At 120F/120F(55C/55C)		
BTU/H (50/60 Hz)	4800	4150/4030
Watts (50/60 Hz)	1408	1217/1181

Operating temperature Range :

Maximum (F/C)	120(55)	120(55)
Minimum (F/C)	-0(-18)	-0(-18)

Airflow at 60 Hz:

Internal loop, CFM (Evaporator)	162	162
External loop CFM (Condenser)	240	240
Refrigerant type	R134A	R134A
Refrigerant charge, oz	16.0	16.0
Sound level at 3 ft, dBA	66.8	66.8

Electrical data

Volts	115	230
Frequency, Hz	60	60
Running Amps at 95F/95F, 60 Hz	11.4	5.5
Running Amps at 120F/120F, 60 Hz	15.0	7.8
Starting Amps (Lock Rotor - LRA)	48	23
Power consumption at 95F/95F, 60 Hz Watts	1132	1091
Power consumption at 120F/120F, 60 Hz Watts	1647	1605
Fuse size, Amps (Maximum)	20	15

Enclosure protection

UL Type Internal loop (Evaporator)	NEMA12	NEMA12
UL Type External loop (Condenser)	NEMA12	NEMA12
Agency approval	cUL listed	cUL listed

Temperature controller

Description	Electronic thermostat	Electronic thermostat
Factory Thermostat setting, F	75	75
Thermostat differential, F	11	11

Unit Construction

Material	Galvanized steel	Galvanized steel
Finish	Textured Baked Powder Grey Paint	Textured Baked Powder Grey Paint

Unit Dimensions

Height, in	10.41	10.41
Width, in	19	19
Depth, in	21.95	21.95
Weight, Lb	97	97