



H10 SERIES HORIZONTAL RACK-MOUNTED AIR-COOLED AIR CONDITIONERS

KA4C3.5H10R w/ s/n above L14A3003

K2A4C3.5H10R w/ s/n above K15A3548

TECHNICAL DATA

Model	UL/CUR Listed or Recognized	BTU/H Capacity	95/95 Rating	Ambient Temp.		Volts	Hz	Running Amps	Fuse Size (Amps)	Approx. Weight lbs. kg.
				°F Max./Min	°C Max./Min					
KA4C3.5H10R	Recognized	3500	3516	120/50	49/10	115/100	60/50	10.0	15	95 44
K2A4C3.5H10R	Recognized	3500	3137	125/50	52/10	230/200	60/50	5.1	15	95 44

Rating shown is for operation at maximum ambient temperature.



STANDARD FEATURES


- Baked Powder Finish
- Built-in Condensate Evaporator
- CFC-Free Refrigerant
- Closed-Loop Cooling
- Compressor Short Cycle Protector
- Filter
- Low Ambient Kit
- Programmable Temperature Alarm
- Programmable Thermostat
- UL/CUR Recognized

ACCESSORIES AND OPTIONS

- Filter Re-coating Adhesive
- Internal Corrosion Protection
- Lifting Eyes
- Remote Monitoring
- Remote Thermostat Relay
- Replacement Filters
- Special controls or indicators
- Special materials or finishes
- Special motors, line cords or connectors



PERFORMANCE




Find additional information on this model at kooltronic.com, or use the Technical Documents QR code below.








Technical Documents



H10




- 1 FILTERED CONDENSER AIR INLET (Ambient Air In)
- 2 CONDENSER OUTLET (Warm Ambient Air Out)
- 3 WARM AIR RETURN FROM ENCLOSURE
- 4 COOL AIR OUTLET TO ENCLOSURE



Many popular units are available as 3D solid models for customer system integration. Please contact Kooltronic for details.

Dimensions, inches [mm], are for reference only and subject to change.

h10.qxd (10/29/21) (20369)



H10 SERIES HORIZONTAL RACK-MOUNTED AIR-COOLED AIR CONDITIONERS

KA4C3.5H10R w/ s/n above L14A3003

K2A4C3.5H10R w/ s/n above K15A3548

DESCRIPTION

KOOLTRONIC **H10 Air-Cooled Rack-Mounted Air Conditioners** are particularly suited for applications where internal horizontal mounting is preferred over external panel, door or top mounting.

Air-cooled models are typically mounted internally at either the top or bottom of the cabinet.

KOOLTRONIC **Rack-Mounted Air Conditioners** all include EIA-notched flanges. Air-cooled models are provided with attractive 19-inch wide stainless steel grilles and knurled captive fasteners for easy removal. Grille area is 65% open. If preferred, side rails can be supplied.

Outdoor or corrosive environments require weather protection and/or special internal and external protective features.

For extreme ambient temperatures and/or severely contaminated environments, the use of **Water-Cooled Air Conditioners** is recommended.

KOOLTRONIC also designs and manufactures a variety of Air Conditioners to meet unique specifications. We invite your inquiries about our modification and custom-design capabilities

FEATURES AND BENEFITS (STANDARD)

All models UL/CUR Recognized.

Built-in condensate evaporator eliminates the need for a drain (normal operation*).

CFC-free refrigerant is used in all H10 Air Conditioners.

Closed-loop cooling provides stable temperature control while excluding dust and humidity from the electrical enclosure.

Compressor short-cycling protection extends compressor life.

Low Ambient Kit maintains sufficient operating pressures when ambient temperatures drop below 50°F [10°C].

Programmable temperature alarm to alert if early action required.

Programmable thermostat capable of remote monitoring and control.

* May not be adequate in extremely high humidity with open or leaky enclosure. Overflow condensate drain fitting and hose are included.

FEATURES AND BENEFITS (OPTIONAL)*

Internal corrosion protection to increase reliability in hostile environments.

Remote monitoring provides temperature data for warning of early action required. (Optional Feature on models with a Programmable Thermostat).

Remote thermostat relay for control by a user-supplied control system.

Special paint finishes.

*Contact KOOLTRONIC for more information.

REPLACEMENT FILTERS

The H9/H10 Filter Part No. is 1175F (16.63" x 9.63" x 0.50" [422mm x 244mm x 13mm])

