



## ENCLOSURE AIR CONDITIONERS

# ACCESS SERIES ULTRA-SLIM COOLING UNITS



**NEMA**  
Type 12, 3R



The **Access Series** closed-loop enclosure air conditioners from Kooltronic feature an ultra-slim depth and a compact footprint – ideal for electrical enclosures, control cabinets, or self-service kiosks in environments with egress limitations.

**Access Series** air conditioning units are designed to meet cooling capacities of 1,000 - 3,000 BTU/H and can be configured for applicable enclosure IP designations and voltage needs.

Contact an Enclosure Cooling Specialist to learn more.

## PRODUCT DESIGN SPECIFICATIONS:

### DSP17

### DSP23

### DSP28

Unit Height:	16.61 in.	23.59 in.	28.03 in.
Unit Width:	17.11 in.	20.77 in.	20.44 in.
Unit Depth:	5.43 in.	4.99 in.	7.14 in.
Cooling Capacity:	1,000 BTU/H	2,000 BTU/H	3,000 BTU/H
Target Maximum Ambient:	122° F	122° F	122° F
Voltage/Phase/Frequency*	115/1/60	115/1/60	115/1/60
Refrigerant	R134A	R134A	R134A
Maximum Noise Level	70 dBA	70 dBA	70 dBA
NEMA Rating	12, 3R	12, 3R	12, 3R
Electrical Heater (optional)	325 Watts	500 Watts	500 Watts

\* Alternative Voltage/Phase/Frequency options are available.

## PRIMARY FEATURES:

- Rated for compatibility with NEMA 12 and 3R electrical enclosures.
- Designed to prevent condensation from forming inside the kiosk.
- All models UL/cUL Listed and Recognized, a standard of safety.
- Heavy-duty steel shell with powder-baked finish (ANSI 61 gray).
- High-temperature alarm to alert if early action is required.
- Easily installed via rivet-nut mounting.
- Compressor short cycle protector.
- Internal corrosion protection.
- Custom paint available.

Ultra-Slim Depth

