



## ENCLOSURE AIR CONDITIONERS

# INTRODUCING THE ACCESS SERIES DSP23



**Ultra-Slim  
5" Depth**

**NEMA**  
Type 12, 3R  
(or applicable IP designation)



The new **Access Series** closed-loop air conditioners from Kooltronic feature a remarkably thin 5-inch depth, versatile installation options, and a compact footprint – ideal for limited space enclosures and door-mount applications. The ultra-slim Access Series DSP23 AC unit is designed to meet a cooling capacity of 2,000 BTU/H and can be configured for applicable enclosure IP designations and/or voltage needs.

Contact an Enclosure Cooling Specialist for more information.

## PRODUCT DESIGN SPECIFICATIONS:

	KA4C2DSP23L	KNA4C2DSP23L	K2A4C2DSP23L	K2NA4C2DSP23L
<b>Max. Height</b>	23.58 in.	23.58 in.	23.58 in.	23.58 in.
<b>Max. Width</b>	22.25 in.	22.25 in.	22.25 in.	22.25 in.
<b>Max. Depth</b>	5 in.	5 in.	5 in.	5 in.
<b>Cooling Capacity @ 95/95 °F</b>	2,300 BTU/H	2,300 BTU/H	2,300 BTU/H	2,300 BTU/H
<b>Target Maximum Ambient</b>	122° F	122° F	122° F	122° F
<b>Voltage/Phase/Frequency</b>	115/1/60	115/1/60	208-240/1/60 220-240/1/50	208-240/1/60 220-240/1/50
<b>Refrigerant</b>	R134A	R134A	R134A	R134A
<b>Max. Noise Level</b>	70 dBA	70 dBA	70 dBA	70 dBA
<b>NEMA Rating</b>	12, 3R, or applicable IP designation	12, 3R, or applicable IP designation	12, 3R, or applicable IP designation	12, 3R, or applicable IP designation
<b>Electrical Heater (optional)</b>	500 Watts	500 Watts	325 Watts	325 Watts

## PRIMARY FEATURES:

- Rated for compatibility with NEMA 12 and 3R electrical enclosures.
- Designed to prevent condensation from forming within the cabinet.
- All Access Series models are UL/CUL Listed, a standard of safety.
- CFC-free refrigerant provides a zero ozone depletion potential.
- High-temperature alarm to alert if early action required.
- Compressor short cycle protector.
- Internal corrosion protection.
- Custom solutions available.

## MOUNTING OPTIONS:

